CRC

SAFETY DATA SHEET

1. Identification

Product identifier Hydraulic & Jack Oil - 1 gal

Other means of identification

Product Code No. SL2553 (Item# 1007841)

Recommended use Hydraulic and jack oil

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use. Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	60 - 70
distillates (petroleum), solvent-refined heavy naphthenic		64741-96-4	30 - 40

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Material name: Hydraulic & Jack Oil - 1 gal

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical

attention if symptoms occur.

Skin contact Wash off with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical

attention if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact Rinse immediately with plenty of water, also under the eyelids. Remove contact lenses, if present

and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting without advice from poison

Direct contact with eyes may cause temporary irritation.

control center. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention if symptoms occur. If ingestion of a large amount does occur,

call a poison control center immediately.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

General fire hazards

Use fire-extinguishing media appropriate for surrounding materials.

None known.

During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Cool containers exposed to heat with water spray and remove container, if no risk is involved.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Wear appropriate personal protective equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. When using, do not eat, drink or smoke. Wash contaminated clothing before reuse. Use appropriate container to avoid environmental contamination. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

Material name: Hydraulic & Jack Oil - 1 gal

8. Exposure controls/personal protection

Occupational exposure limits

U.S	OSHA
-----	------

Components	Туре	Value	
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
US. OSHA Table Z-1 Limits for Air C	ontaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	
		500 ppm	
ACGIH			
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit Values			_
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH			
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
,	TWA	5 mg/m3	Mist
US. NIOSH: Pocket Guide to Chemic	al Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.

Biological limit values

Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).

Other Wear suitable protective clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Amber. Red.
Odor Mild petroleum.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

680 °F (360 °C) estimated

Flash point 380 °F (193.3 °C) Pensky-Martens Closed Cup

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

110t available

Flammability limit - upper

(%)

Not available.

Vapor pressure 0.004 hPa estimated

Vapor density > 5 (air = 1) Relative density 0.87 - 0.89

Solubility(ies)

Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available.

Viscosity 49.8 - 58 mm²/s (104 °F (40 °C))

Percent volatile 99 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

Material name: Hydraulic & Jack Oil - 1 gal
No. SL2553 (Item# 1007841) Version #: 01 Issue date: 12-17-2019

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged or excessive inhalation may cause respiratory tract irritation.

Skin contact Prolonged skin contact may cause temporary irritation. Repeated exposure may cause skin

dryness or cracking.

Direct contact with eyes may cause temporary irritation. Eve contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results	
Hydraulic & Jack Oil - 1 gal			
<u>Acute</u>			
Dermal			
LD50	Rabbit	5034 mg/kg	
Oral			
LD50	Rat	8806 mg/kg	
Components	Species	Test Results	

distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Oral

Rat LD50 > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-54-7)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Not classified.

Aspiration hazard

repeated exposure

Not classified.

Chronic effects Prolonged inhalation may be harmful.

No. SL2553 (Item# 1007841) Version #: 01 Issue date: 12-17-2019

Further information This product has no known adverse effect on human health.

^{*} Estimates for product may be based on additional component data not shown.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Test Results Components **Species**

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) > 10000 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty **Disposal instructions**

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CERCLA Hazardous Substance List (40 CFR 302.4)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: Hydraulic & Jack Oil - 1 gal

No. SL2553 (Item# 1007841) Version #: 01 Issue date: 12-17-2019

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Massachusetts RTK - Substance List

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

US. Pennsylvania Worker and Community Right-to-Know Law

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

Not determined

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

Material name: Hydraulic & Jack Oil - 1 gal

SDS US

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-17-2019
Prepared by Dustin Kern

Version # 01

DisclaimerThe information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: Hydraulic & Jack Oil - 1 gal