



## Material Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)

ID: 82658

### \*\*\* Section 1 - Chemical Product and Company Identification \*\*\*

**Product Code:** 6605, 6616

**Product Use:** Cleaning and degreasing metal parts. If this product is used in combination with other products, refer to the Material Safety Data Sheet for those products.

**Synonyms:** Safety-Kleen Premium Gold Solvent. Parts Washer Solvent; Petroleum Distillates; Petroleum Naphtha; Naphtha, Solvent; Stoddard Solvent; Mineral Spirits.

Safety-Kleen Systems, Inc.  
2600 North Central Expressway  
Suite 400  
Richardson, TX 75080

Phone: 1-800-669-5740

Emergency # 1-800-468-1760  
www.safety-kleen.com

**Issue Date**

November 8, 2012

**Supersedes Issue Date**

January 20, 2012

**Original Issue Date**

January 26, 1995

PREPARED BY: Product MSDS Coordinator      APPROVED BY: MSDS Task Force

### \*\*\* Section 2 - Hazardous Identification \*\*\*

#### EMERGENCY OVERVIEW

**Appearance**

Liquid, clear, colorless to pale yellow, mild hydrocarbon odor.

**Signal Word**

WARNING!

**Physical Hazards**

Combustible liquid and vapor.

**Health Hazards**

May be harmful if inhaled. May irritate the respiratory tract (nose, throat, and lungs), eyes, and skin. May be harmful if swallowed. Contains material that may cause central nervous system and kidney damage.

#### POTENTIAL HEALTH EFFECTS

**Inhalation (Breathing)**

High concentrations of vapor may be harmful if inhaled. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

**Eyes**

May cause irritation.

**Skin**

May cause irritation. Not likely to be absorbed in harmful amounts.

**Ingestion (Swallowing)**

May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and central nervous system effects as noted under **INHALATION (BREATHING)**. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

**Medical Conditions Aggravated by Exposure**

Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, kidney, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

# Material Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)

ID: 82658

## Chronic

Prolonged or repeated inhalation may cause toxic effects as noted under **INHALATION (BREATHING)**.  
Prolonged or repeated exposure may cause central nervous system and kidney damage. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis).  
Prolonged or repeated skin contact may cause drying, cracking, redness, itching, swelling (dermatitis) and or burns.

## Cancer Information

No known carcinogenicity. For more information, see **SECTION 11: CARCINOGENICITY**.  
Also see **SECTION 15: CALIFORNIA**.

## Environmental Hazards

Product is not toxic to aquatic life. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

### \*\*\* Section 3 - Composition / Information on Ingredients \*\*\*

CAS	Component	Percent
64742-47-8	Distillates (petroleum), hydrotreated light	100

## Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Stoddard solvent (8052-41-3).

### \*\*\* Section 4 - First Aid Measures \*\*\*

## Inhalation (Breathing)

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

## Eyes

If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

## Skin

Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.

## Ingestion (Swallowing)

Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything by mouth to an unconscious person.

## Notes to Physicians

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

### \*\*\* Section 5 - Fire Fighting Measures \*\*\*

## Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.

## Conditions of Flammability

Heat, sparks, or flame.

## Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

## Protective Equipment For Firefighting

Firefighters should wear full-face, self contained breathing apparatus and impervious protective clothing.  
Firefighters should avoid inhaling any combustion products.

## Fire Fighting Equipment/Instructions

Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

# Material Safety Data Sheet

Material Name: **SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)**

ID: 82658

**NFPA Ratings: Health: 1 Fire: 2 Reactivity: 0**

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## Fire and Explosion Hazards

Vapor explosion hazard indoors, outdoors, or in sewers. Vapors may travel to ignition source and flashback. Vapors will spread along the ground and collect in low or confined areas. Run-off to sewer may create a fire hazard. Heated containers may rupture or be thrown into the air. "Empty" containers may retain residue and can be dangerous. Products are not sensitive to mechanical impact. Products may be sensitive to static discharge, which could result in fire or explosion.

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Handling Procedures

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.

### Shipping and Storing

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous. See **SECTION 14: TRANSPORTATION INFORMATION** for Packing Group information.

## \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

### Exposure Guidelines

#### Component Exposure Limits

##### Distillates (petroleum), hydrotreated light (64742-47-8)

ACGIH:	100 ppm TWA (related to Stoddard solvent)
OSHA Final:	500 ppm TWA; 2900 mg/m <sup>3</sup> TWA (related to Stoddard solvent)
OSHA Vacated:	100 ppm TWA; 525 mg/m <sup>3</sup> TWA (related to Stoddard solvent)
NIOSH:	350 mg/m <sup>3</sup> TWA (related to Stoddard solvent) 1800 mg/m <sup>3</sup> Ceiling (15 min, related to Stoddard solvent)

### Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

### Personal Protective Equipment: Respiratory

Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

### Personal Protective Equipment: Eyes/Face

Where eye contact is likely, wear chemical goggles; contact lens use is not recommended.

# Material Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)

ID: 82658

## Personal Protective Equipment: Skin

Where skin contact is likely, wear neoprene, nitrile, or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended.

To avoid prolonged or repeated contact with products where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

## Personal Protective Equipment: Personal Hygiene

Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, and/or protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with this product.

## Other Personal Protective Equipment

Where spills and splashes are likely, facilities storing or using these products should be equipped with an emergency eyewash and shower, both equipped with clean water, in the immediate work area.

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

<b>Appearance/Odor :</b> Liquid, clear, colorless to pale yellow, mild hydrocarbon odor .	<b>pH:</b> Not applicable.
<b>Boiling Point:</b> 350°F (177°C) (initial)	<b>Melting Point:</b> -45°F (-43°C) (maximum)
<b>Solubility (H2O):</b> Insoluble.	<b>Specific Gravity:</b> 0.77 to 0.82 at 60°F (15.6°C) (water = 1)
<b>Density:</b> 6.4 to 6.7 LB/US gal (770 to 800 g/l)	<b>Octanol/H2O Coeff.:</b> Not available.
<b>Evaporation Rate:</b> <0.1 (butyl acetate = 1)	<b>Molecular Weight:</b> Not available.
<b>Odor Threshold:</b> 30 ppm (based on Stoddard Solvent)	<b>Auto Ignition:</b> 480°F (249°C) (minimum)
<b>LFL:</b> 0.7 VOL% (minimum)	<b>Flash Point:</b> 148°F (64°C) (minimum)
<b>UFL:</b> 5 VOL% (maximum)	
<b>Vapor Pressure:</b> 0.2 mm Hg at 68°F (20°C) 0.6 mm Hg at 100°F (37°C)	

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

### Stability

Stable under normal temperatures and pressures.

### Incompatibility

Avoid acids, alkalis, oxidizing agents, reducing agents, or reactive halogens.

### Reactivity

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

### Hazardous Decomposition Products

None under normal temperatures and pressures. See also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS**.

### Conditions To Avoid

Avoid heat, sparks, or flame.

## \*\*\* Section 11 - Toxicological Information \*\*\*

### Toxicity Data

#### Component Analysis - LD50/LC50

**Distillates (petroleum), hydrotreated light (64742-47-8)**

Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

### Acute Effects

May be harmful if inhaled. May irritate the respiratory tract (nose, throat, and lungs), eyes, and skin. May be harmful if swallowed. Contains material that may cause central nervous system and kidney damage. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

### Repeated Dose Effects

Prolonged contact may cause kidney or central nervous system damage.

# Material Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)

ID: 82658

## Carcinogenicity

### Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

### Target Organ Effects

Product can irritate skin and eyes. Product can be aspirated into lungs.

### Mutagenicity

Based on best current information, there is no known mutagenicity associated with this product.

### Teratogenicity

Based on best current information, there is no known teratogenicity associated with this product.

## \*\*\* Section 12 - Ecological Information \*\*\*

### Ecotoxicity

A Static Acute Bioassay as per California Department of Fish and Game WPCL was done using fathead minnows and up to 750 ppm of the products in water. The material passed the bioassay.

### Component Analysis - Ecotoxicity - Aquatic Toxicity

#### Distillates (petroleum), hydrotreated light (64742-47-8)

Duration/Test/Species	Concentration/Conditions/Notes
96 Hr LC50 Pimephales promelas	45 mg/L [flow-through]
96 Hr LC50 Lepomis macrochirus	2.2 mg/L [static]
96 Hr LC50 Oncorhynchus mykiss	2.4 mg/L [static]

### Persistence/Degradability

Product is not expected to be readily biodegradable.

### Bioaccumulation/Accumulation

Product is not expected to bioaccumulate.

### Mobility in Environmental Media

Product is expected to have high soil mobility.

### Other Adverse Effects

No information available for the product.

## \*\*\* Section 13 - Disposal Considerations \*\*\*

### Disposal Instructions

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

### US EPA Waste Number & Descriptions

Not regulated. Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product.

## \*\*\* Section 14 - Transportation Information \*\*\*

### Emergency Response Guide Number

128 Reference .North American Emergency Response Guidebook

### DOT

**Bulk Packages (>119 Gallons): Shipping Name:** Combustible liquid, n.o.s. (petroleum naphtha) **UN/NA #:** NA1993. **Hazard Class:** Combustible liquid. **Packing Group:** III **Required Placards:** Class 3, NA1993

**Non-bulk Packages (<120 Gallons): Shipping Name:** Cleaning compounds (Petroleum naphtha) (Not US DOT regulated). **UN/NA #:** None. **Hazard Class:** None **Packing Group:** None **Required Label(s):** None

**Shipping Name:** Non-regulated goods.

### TDG

**Shipping Name:** Not regulated as a dangerous good.

# Material Safety Data Sheet

Material Name: SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)

ID: 82658

## IATA Information

No Classification Assigned.

## IMDG Information

No Classification Assigned.

### \*\*\* Section 15 - Regulatory Information \*\*\*

#### Volatile Organic Compounds (As Regulated)

100 WT%; 6.4-6.7 LB/US gal; 770-800 g/l

As per 40 CFR Part 51.100(s)

VOC Vapor Pressure Approx 0.2 mmHg @20°C

Product may or may not be considered photochemically reactive (100% by weight). Consult your state or local air district regulations for location specific information.

#### SARA Sections 311/312

This product poses the following health hazards as defined in 40 CFR Part 370 and are subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard

Delayed (Chronic) Health Hazard

Fire Hazard

#### SARA 302/304

##### Component Analysis

This product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

#### SARA Section 313

This product does not contain "toxic" chemicals subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

##### Component Analysis

This product does not contain any "toxic" chemical subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

## CERCLA

##### Component Analysis

This product does not contain any "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

## TSCA

The component of this product is listed on, or is automatically included as "naturally occurring chemical substances" on, or is exempted from the requirement to be listed on, the TSCA Inventory.

##### Component Analysis

Component	CAS #	TSCA
Distillates (petroleum), hydrotreated light	64742-47-8	Yes

## State Regulations

This product may contain a detectable amount of benzene CAS 71-43-2, p-dichlorobenzene CAS 106-46-7, ethylbenzene CAS 100-41-4, and naphthalene CAS 91-20-3. WARNING: These chemicals are known to the State of California to cause cancer.

This product may contain a detectable amount of benzene CAS 71-43-2 and toluene CAS 108-88-3. WARNING: These chemicals are known to the State of California to cause birth defects or other reproductive harm.

## U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	MA	MN	NJ	PA	CA
Distillates (petroleum), hydrotreated light (*related to: Stoddard solvent)	64742-47-8	Yes <sup>1</sup>	Yes <sup>1</sup>	Yes <sup>1</sup>	Yes <sup>1</sup>	Yes <sup>1</sup>

# Material Safety Data Sheet

Material Name: **SAFETY-KLEEN PREMIUM SOLVENT  
(VIRGIN AND RECYCLED)**

ID: 82658

## Canadian Regulations

This product have been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

## Component Analysis

Component	CAS #	CAN
Distillates (petroleum), hydrotreated light	64742-47-8	DSL

## Canadian WHMIS Information

Class B3 - Combustible Liquid Class D2B - Irritating to eyes and skin.

## Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:  
**Distillates (petroleum), hydrotreated light (64742-47-8)** 1 % (related to Stoddard solvent)

## Canadian Environmental Protection Act (CEPA)

The component of this product is listed on, or is automatically included as "substance occurring in nature" on, or is exempted from the requirements to be listed on, the Canadian Domestic Substances List (DSL).

## \* \* \* Section 16 - Other Information \* \* \*

## Label/Other Information

These products are United States Department of Agriculture (USDA) approved and ETL classified.

## Revision Information

Product name, synonyms, supplier address.

## Disclaimer

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplier to the user.

End of Sheet 82658