# CRC

# SAFETY DATA SHEET

# 1. Identification

Product identifier Air Tool Oil

Other means of identification

Product code SL2531, SL2533

Recommended use Lubricant for pneumatic equipment

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical
 800-521-3168

**Assistance** 

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

# 2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

**Hazard statement** The mixture does not meet the criteria for classification.

**Precautionary statement** 

**Prevention** Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use. Observe good industrial hygiene practices.

**Response** Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

# 3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light Naphthenic		64742-53-6	90 - 100
Distillates (petroleum), solvent-refined heavy naphthenic		64741-96-4	3 - 5
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts		68649-42-3	1 - 3

Material name: Air Tool Oil SDS US

SL2531, SL2533 Version #: 01 Issue date: 10-23-2015

# 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical

attention if symptoms occur.

Skin contact Wash off with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical

attention if irritation develops and persists. Wash contaminated clothing before reuse.

Rinse immediately with plenty of water, also under the eyelids. Remove contact lenses, if present Eye contact

and easy to do. Get medical attention if irritation develops and persists.

Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting without advice from poison Ingestion

control center. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention if symptoms occur. If ingestion of a large amount does occur,

call a poison control center immediately.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special Treat symptomatically.

treatment needed **General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

and precautions for firefighters Fire fighting

Cool containers exposed to heat with water spray and remove container, if no risk is involved.

equipment/instructions General fire hazards

No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Wear appropriate personal protective equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. When using, do not eat, drink or smoke. Wash contaminated clothing before reuse. Use appropriate container to avoid environmental contamination. For product usage instructions, please see the product label.

Conditions for safe storage. including any incompatibilities Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

Material name: Air Tool Oil SDS US

SL2531, SL2533 Version #: 01 Issue date: 10-23-2015

cupational exposure limits			
US. OSHA Table Z-1 Limits Components	s for Air Contaminants (29 CFR 1910.100) Type	0) Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	PEL	2000 mg/m3 500 ppm 5 mg/m3	Mist.
		2000 mg/m3 500 ppm	
US. ACGIH Threshold Lim Components	it Values Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide Components	to Chemical Hazards Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m3	
•	STEL	10 mg/m3	Mist.
Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
logical limit values	No biological exposure limits noted for the	he ingredient(s).	
propriate engineering htrols	Good general ventilation (typically 10 air should be matched to conditions. If appl or other engineering controls to maintair exposure limits have not been established General ventilation normally adequate.	icable, use process enclosur n airborne levels below recor	es, local exhaust ventilation nmended exposure limits. I
ividual protection measure Eye/face protection	s, such as personal protective equipmen Wear safety glasses with side shields (c		
Skin protection Hand protection	Wear protective gloves such as: Nitrile.	Polyvinyl chloride (PVC).	
Other	Wear suitable protective clothing.	, , ( )-	
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.		
Thermal hazards	Wear appropriate thermal protective clo		
neral hygiene	Handle in accordance with good industri	-	ce.

# 9. Physical and chemical properties

# **Appearance**

considerations

Material name: Air Tool Oil SDS US 3/8 SL2531, SL2533 Version #: 01 Issue date: 10-23-2015

**Physical state** Liquid. **Form** Liquid. Color Amber.

Odor Mild petroleum. **Odor threshold** Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

680 °F (360 °C) estimated

320 °F (160 °C) Cleveland Open Cup Flash point

**Evaporation rate** Slow.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available. Flammability limit - lower

(%)

Not available.

Flammability limit - upper (%)

Not available. Vapor pressure > 1 (air = 1)Vapor density 0.9 - 0.92Relative density Solubility (water) Insoluble. **Partition coefficient** 

(n-octanol/water)

**Viscosity (kinematic)** 

Not available.

Not available.

**Auto-ignition temperature** 

500 °F (260 °C) estimated

**Decomposition temperature** 

22.5 - 27.5 mm<sup>2</sup>/s (104 °F (40 °C))

Percent volatile Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

# 11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged or excessive inhalation may cause respiratory tract irritation.

Prolonged skin contact may cause temporary irritation. Repeated exposure may cause skin Skin contact

dryness or cracking.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

**Acute toxicity** Not available.

Material name: Air Tool Oil SDS US Product Species Test Results

Air Tool Oil

Acute Dermal

LD50 Rabbit 5100 mg/kg estimated

Inhalation

LC50 Rat 2295 mg/m³, 4 hours estimated

Oral

LD50 Rat 5097 mg/kg estimated

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not classified.

**Chronic effects** Prolonged inhalation may be harmful.

**Further information** This product has no known adverse effect on human health.

# 12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the
•	possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
Air Tool Oil			
Aquatic			
Crustacea	EC50	Daphnia	99.9848 mg/l, 48 hours estimated
Fish	LC50	Fish	549.3577 mg/l, 96 hours estimated
Components		Species	Test Results

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1 - 5 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 1 - 5 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** 

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Material name: Air Tool Oil SDS US

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# 13. Disposal considerations

Disposal of waste from

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty residues / unused products

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

# 15. Regulatory information

# US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

# SARA 304 Emergency release notification

Not regulated.

#### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

# **CERCLA Hazardous Substance List (40 CFR 302.4)**

Phosphorodithioic acid. O.O-di-C1-14-alkvl esters, zinc Listed.

salts (CAS 68649-42-3)

### **CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**Food and Drug** 

Not regulated.

Administration (FDA)

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - No Delayed Hazard - No **Hazard categories** Fire Hazard - No Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely No hazardous substance

# **US** state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

Material name: Air Tool Oil SDS US

# US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

#### **US. Massachusetts RTK - Substance List**

Distillates (petroleum), Hydrotreated Light Naphthenic (CAS 64742-53-6) Distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

# US. New Jersey Worker and Community Right-to-Know Act

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

# **US. Rhode Island RTK**

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (CAS 68649-42-3)

# US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

# **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# Volatile organic compounds (VOC) regulations

#### **EPA**

VOC content (40 CFR

Not determined

51.100(s))

**Consumer products** (40 CFR 59, Subpt. C) Not regulated

Inventory name

State

**Consumer products** Not regulated 0 % VOC content (CA) 0 % VOC content (OTC)

# **International Inventories**

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

On inventory (yes/no)\*

# 16. Other information, including date of preparation or last revision

Issue date 10-23-2015 Prepared by Allison Cho

Version # 01

**Further information** Not available. **HMIS®** ratings Health: 1 Flammability: 1

Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name: Air Tool Oil SDS US

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# **NFPA** ratings



#### Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.

Material name: Air Tool Oil