

OSHA (TWA) - N/E ACGIH (PEL) - 500 ppm

PB Penetrating Catalyst

MSDS Number: PB - Aerosol

Revision Date: 10/16

Page 1

PRODUCT AND COMPANY IDENTIFICATION

Product Name:

PB Penetrating Catalyst

Revision Date:

10/16/07

MSDS Number: **Common Name:** PB - Aerosol PB Blaster

Product Code:

16-PB, 8-PB, 8-PBS, PBTS, 20-PB, 26-PB

Manufacturer:

The Blaster Chemical Companies, Inc.

8500 Sweet Valley Drive Valley View, Ohio 44125

(216) 901-5800 (216) 901-5801 fax

www.blasterproducts.com

24 Hour emergency contact: Chemtrec (800) 424-9300

Hydrotreated Light Distillate

COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Percent	Exposure Limits
Alkyloxypolyethyleneoxyethanol	68131-40-8	0-3%	OSHA (TWA)- N/E ACGIH (TLV)- N/E
Solvent Naphtha, Heavy Aromatic**	64742-94-5	40-50%	OSHA (TWA)- N/E ACGIH (TWA)- N/E
Heavy Petroleum Distillate	64742-65-0	20-30%	OSHA (TWA)-N/E ACGIH (TLV)- N/E

*Denotes chemical is subject to the reporting requirements of SECTION 313 of Title III of the 1986 Super fund Amendments and Reauthorization Act (SARA) and 40 CFR PART 372.

** Aromatic Naphtha contains 1-7 % Naphthalene (91-20-3) and 0-1% Pseudocumene (95-63-6)

64742-47-8 30-40%

HAZARDS IDENTIFICATION

Route of Entry:

Eyes, skin, inhalation, ingestion

Target Organs: Inhalation:

Inhalation of spray mist may cause irritation to the respiratory tract.

Skin Contact:

Repeated or prolonged contact with skin may cause mild irritation and possibly dermatitis.

Eye Contact:

Likely to cause immediate or delayed irritation. Irritation will show as redness and/or swelling of t

eyes.

Ingestion may cause irritation to the mouth, esophagus and stomach.

Ingestion:



PB Penetrating Catalyst

MSDS Number: PB - Aerosol

Revision Date: 10/16

Page 2 of

May aggravate pre-existing skin and respiratory disorders.

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fata

4 FIRST AID MEASURES

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxyg

Continue to monitor. Get medical attention.

Skin Contact:

Remove contaminated clothing immediately! Wash skin with soap and water. If irritation devel

seek medical attention.

Eye Contact:

Flush eye(s) with water for 15 minutes. Get medical attention. If eye irritation persists, obtain

medical treatment.

Ingestion:

Do not induce vomiting! Get medical attention immediately!

5 1 1 1 FIRE FIGHTING MEASURES

Flash point: 155°F ASTM D-56 (TCC)

Extinguishing Media: Dry chemical, carbon dioxide or foam is recommended. Water may be ineffective for extinguishmer but can be useful in minimizing or dispersing vapors, protecting personnel and cooling containers. If containers are not properly cooled they can rupture in the heat of a fire. Avoid spreading burning liquid with water used for cooling purposes.

Unusual Fire & Expolsion Hazards: Level 3 Aerosols - Contents Under Pressure!

GMM ACCIDENTAL RELEASE MEASURES

Leaking aerosol cans should be put into suitable container until the internal pressure has dissipated. Use suitable absorber to collect liquid product. Consult regulations for the disposal of the container, liquid and absorbents.

7 HANDLING AND STORAGE

Handling Precautions:

Use in accordance with good industrial workplace practices. Avoid unnecessary contact

Wash thoroughly after handling. Use with good ventilation.

Storage Requirements:

Store in a dry place away from excessive heat. Store containers with lids on and proper

labeled.

Do not store at temperatures above 120 degrees F.



PB Penetrating Catalyst

MSDS Number: PB - Aerosol

Revision Date: 10/16

Page 3

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Protective Equipment:

Eye wash stations and emegrency showers should be immediately available.

Eyes and Face: Standard safety glasses with splash shields typically offer adequate protection. Where excessive splashing or spraying is possible, a face shield should used.

Skin and clothing: Excessive contact should be avoided. Neoprene gloves, boots at aprons will provide adequate protection when contact cannot be avoided. Remove a wash any contaminated clothing immediately. Wash thoroughly after handling.

Respiratory: Good general ventilation should be sufficient to control airborne levels. Maintain airborne concentrations below OSHA established exposure limits of ingredients in Section 2.

Exposure Guidelines/Other:

The Blaster Chemical Companies takes no responsibility for determining what measures are required for personal protection in any specific application. This information should be used with discretion.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Orange viscous oily

Physical State:

Liquid

Boiling Point:

352 F

Odor:

Heavy aromatic

Freezing/Melting Pt.:

Not determined

pH:

Not determined

Solubility:

nil

Vapor Pressure:

Not determined

Spec Grav./Density:

0.87 (water = 1)

Vapor Density:

>1 (air = 1)

Heat Value:

VOC:

Evap. Rate:

Bulk Density:

Octanol:

Octenion.

Molecular Weight:

Particle Size:

Softening Point:

Viscosity:

Percent Volatile:

Sat. Vap. Concentrat.:

Molecular Formula:

Not determined

Not determined

<1 (NBA = 1)

Not determined Not applicable

Not determined

Not applicable

Not applicable

Not determined

Not determined

Not determined

Not determined



PB Penetrating Catalyst

MSDS Number: PB - Aerosol

Revision Date: 10/16

Page 4

10 STABILITY AND REACTIVITY

Stability:

This product is stable.

Conditions to avoid:

Avoid excessive heat, sources of ingition and excessive water.

Materials to avoid (incompatability):

Avoid contact with strong oxidizing agents and strong reducing agents (stro

acids or bases.) Avoid mixture with water.

Hazardous Decomposition products:

Carbon monoxide, carbon dioxide, and various hydrocarbons.

Hazardous Polymerization:

Will not occur.

TOXICOLOGICAL INFORMATION

Toxicological information on this product as a mixture has not been determined. See section 15 for reportable ingredients.

12 11 12 ECOLOGICAL INFORMATION

Ecological information on this product as a mixture has not been determined.

13 DISPOSAL CONSIDERATIONS

Used or unused product should be disposed of in accordance with local, state, and federal regulations. Some special regulations may exists for the disposal of empty aerosol containers.

Empty containers may contain residual pressure and contents. They should be handled with the same precautions as the product.

14 Manual TRANSPORT INFORMATION

Dept. of Transportation (DOT):

This product, as it leaves Blaster's facilities, meets the definitions set forth in CFR 49 part 173.150c as a "consumer commodity." Allowing for certain exceptions (173.156) for domestic surface (ground) shipments.

Proper shipping name: Consumer Commodity

Hazard class:

ORM-D

International (INDT-IATA):

Proper shipping name: Aerosols, Limited Quantities Hazard class: 2 Flammable Compressed Gas

UN Number:

1950



PB Penetrating Catalyst

MSDS Number: PB - Aerosol

Revision Date: 10/16

Page 5 of

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742650 40-60%) NJHS

*Carbon dibmide (propellant) (124389 0-3%) MASS, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXATR = TX Air Contaminants with Health Effects Screening Level

月3 トン ル A OTHER INFORMATION

Manufacturer's Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither The Blaster Chemical Companies nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists.

HMIS Ratings:

NFPA Ratings:

Health: 2

2

Health: Fire:

2

Fredericking: (

Reacitivity:

END OF MSDS DOCUMENT